



2K FxLiner Bedliner

Products Characteristics

- Excellent shock and scratch resistance
- Highly resistant to fuels, chemicals and oils
- Excellent adhesion to most surfaces
- Easy to clean
- Excellent water
- Available in most colours

Properties

Product Type	Polvurethane Bedliner
Coverage	8m2 per litre @ 60um DFT
Drying times @20C	
<i>Flash Off</i>	20 minutes
<i>Dust Free</i>	60 minutes
<i>Baking</i>	30 minutes @ 60°C

The drying time depends on temperature, humidity and the thickness of the applied coat.

Available colours:



Black White Silver Grey Red

Most colours available upon request

We recommend Buzzweld 2K Tintable Epoxy for most substrates except plastics. Call for more info.

Surface Preparation

- De-rust, abrade and clean surfaces prior to coating
- The surface must be free from all contamination including rust, grease and moisture.
- Before use, carefully read and note the warning text on the label.

Contact:

WWW.BUZZWELD.CO.UK
ENQUIRIES@BUZZWELD.CO.UK
Unit 10, Brunel Court, Yate, Bristol
01454 315588

Environmentally sound

The products supplied by Buzzweld are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

Nozzle: 1.8-2mm (fine texture)
2.5mm (coarse texture)

Pressure: 2 bar (30 PSI)

Distance from object: Min 20cm
Number of coats 2-3 coats. 1st coat applied as an even wet coat, 2nd coat reduce pressure to achieve finish

Flash off between coats 10-15 minutes @ 20°C H