



2K High Build Tintable Epoxy

Products Characteristics

- Epoxy -polyamide with activated zinc-phosphates
- High etching adhesion
- High resistance to chemicals
- High spray quality
- Long overcoating
- Available in most colours

Properties

Product Type	Epoxy Primer
Coverage	7m ² per litre @ 50um DFT
Drying times @20C	
<i>Flash Off</i>	10 minutes
<i>Dust Free</i>	30minutes
<i>Overcoating Window</i>	6hrs to max 96hrs,

The drying time depends on temperature, humidity and the thickness of the applied coat.

Available colours:



Black White Silver Grey Red

Most colours available upon request

Surface Preparation

- De-rust, abrade and clean surfaces prior to coating
- The surface must be free from all contamination including rust, grease and moisture.
- Before use, carefully read and note the warning text on the label.

Contact:

WWW.BUZZWELD.CO.UK
ENQUIRIES@BUZZWELD.CO.UK
Unit 10, Brunel Court, Yate, Bristol
01454 315588

Environmentally sound

The products supplied by Buzzweld are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.