



Mastic tint pro - Schultz

1Litre

Products Characteristics

- Products Characteristics
- Excellent corrosion prevention
- Long lasting elasticity
- Noise Insulation
- Excellent adhesion
- Overcoatable
- Resistant to acids and alkalines
- Good weathering resistance

Properties

Product Type	Rubberised resin
Coverage	1.56 - 2.19m ² per 500ml
Temp resistant	110°C
Drying times	
<i>Dust Free</i>	30 minutes
<i>Touch Dry</i>	60 minutes
<i>Sandable</i>	after 2 hours
<i>Overcoatable</i>	after 2 hours

The drying time depends on temperature, humidity and the thickness of the applied coat.

Surface Preparation

- De-rust, abrade and clean surfaces prior to coating
- The surface must be free from all contamination including rust, grease and moisture.
- Before use, carefully read and note the warning text on the label.

Contact:

WWW.BUZZWELD.COM
CRAIG@BUZZWELD.COM
Hatherley, Yate, Bristol BS37 4LT
01454 600602

Environmentally sound

The products supplied by Buzzweld are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

