



SAFETY DATA SHEET Buzzweld DTM (Lead-Free Colours)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **Buzzweld DTM (Lead-Free Colours)**
 Product number BUZDTM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PC 9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Supplier Buzzweld, Unit 10,
 Brunel Court, Dean road,
 Yate,
 Bristol
 BS375PD
 Tel: +44 (0)1454537637

Contact person enquiries@buzzweld.co.uk

1.4. Emergency telephone number

Emergency telephone United Kingdom: 01454537637 (Mon-Fri 0800 - 1700 hrs).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226
 Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 -
 H315
 Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements EUH208 Contains METHYL ETHYL KETOXIME, COBALT BIS(2-ETHYLHEXANOATE).
 May produce an allergic reaction.
 H226 Flammable liquid and vapour.
 H332 Harmful if inhaled.
 H315 Causes skin irritation.
 H411 Toxic to aquatic life with long lasting effects.

Buzzweld DTM (Lead-Free Colours)

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P391 Collect spillage.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains XYLENE

Other information

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

XYLENE			30-60%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 012119488216-32-0000	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Asp. Tox. 1 - H304			
ETHYLBENZENE			5-10%
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 012119489370-35-0000	
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 STOT RE 2 - H373 Asp. Tox. 1 - H304			
TRIZINC BIS(ORTHOPHOSPHATE)			1-5%
CAS number: 7779-90-0	EC number: 231-944-3	REACH registration number: 012119485044-40-XXXX	
M factor (Acute) = 1	M factor (Chronic) = 1		

Buzzweld DTM (Lead-Free Colours)

Classification Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410			
METHYL ETHYL KETOXIME <1%			
CAS number: 96-29-7	EC number: 202-496-6	REACH registration number: 012119539477-28-0000	
Classification Acute Tox. 4 - H312 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 2 - H351			
COBALT BIS(2-ETHYLHEXANOATE) <1%			
CAS number: 136-52-7	EC number: 205-250-6	REACH registration number: 012119524678-29-0000	
M factor (Acute) = 1			
Classification Eye Irrit. 2 - H319 Skin Sens. 1A - H317 Repr. 1B - H360F Aquatic Acute 1 - H400 Aquatic Chronic 3 - H412			

The full text for all hazard statements is displayed in Section 16.

Composition comments	The data shown are in accordance with the latest EC Directives.
Ingredient notes	This mixture contains $\geq 1\%$ titanium dioxide (CAS 13463-67-7). The Annex VI classification of titanium dioxide does not apply to this mixture according to its Note 10.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
Inhalation	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Immediately remove contaminated clothing. Rinse immediately with plenty of water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	No data available on the mixture itself.
---------------------	--

Buzzweld DTM (Lead-Free Colours)

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Heating may generate flammable vapours.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon dioxide (CO₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting Move containers from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment protective for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from oxidising materials, heat and flames.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters Occupational exposure limits

XYLENE

Buzzweld DTM (Lead-Free Colours)

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk) Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk) Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 50 ppm 221 mg/m³ Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 100 ppm 442 mg/m³

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³
Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³
Sk

Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 100 ppm 442 mg/m³ Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 200 ppm 884 mg/m³

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

Ingredient comments WEL = Workplace Exposure Limits

HYDROCARBONS, C9, AROMATICS (CAS: 64742-95-6)

DNEL

Workers - Dermal; Long term systemic effects: 25 mg/kg bw/day
Workers - Oral; Long term systemic effects: 150 mg/m³
Consumer - Dermal; Long term systemic effects: 11 mg/kg
bw/day Consumer - Inhalation; Long term : 32 mg/m³

METHYL ETHYL KETOXIME (CAS: 96-29-7)

DNEL

Workers - Dermal; Short term systemic effects: 2.5 mg/kg/day
Workers - Dermal; Long term systemic effects: 1.3 mg/kg/day
Workers - Inhalation; Long term systemic effects: 9 mg/m³
Workers - Inhalation; Long term local effects: 3.33 mg/m³
Consumer - Dermal; Short term systemic effects: 1.5 mg/kg/day
Consumer - Dermal; Long term systemic effects: 0.78 mg/kg/day
Consumer - Inhalation; Long term systemic effects: 2.7 mg/m³
Consumer - Inhalation; Long term local effects: 2 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

If a risk assessment indicates eye contact is possible, suitable eye protection should be worn e.g. safety spectacles, safety goggles or a faceshield as appropriate. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Buzzweld DTM (Lead-Free Colours)

Hand protection	Use protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber; thickness 0.35mm minimum. Butyl Rubber; thickness 0.5mm minimum. Fluorinated rubber (Viton); thickness 0.4mm minimum. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. The breakthrough time for any glove material may be different for different glove manufacturers. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. Check that the respirator fits tightly and the filter is changed regularly.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Various colours.
Odour	Characteristic.
Initial boiling point and range	130°C
Flash point	25°C Closed cup.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.6% Upper flammable/explosive limit: 7.0%
Vapour pressure	Not available.
Relative density	1.00 - 1.20
Solubility(ies)	Immiscible with water.
Partition coefficient	Not available.
Viscosity	Kinematic viscosity > 20.5 mm ² /s.

9.2. Other information

Other information	No additional information
Volatile organic compound	This product contains a maximum VOC content of 580 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Flammable/combustible materials.
------------	----------------------------------

10.2. Chemical stability

Buzzweld DTM (Lead-Free Colours)

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Acids. Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects Acute toxicity - dermal

ATE dermal (mg/kg) 3,045.73

Acute toxicity - inhalation

ATE inhalation (gases ppm) 10,590.82

ATE inhalation (vapours mg/l) 25.89

ATE inhalation (dusts/mists mg/l) 3.53

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Harmful by inhalation. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Product has a defatting effect on skin. Irritating to skin. May cause an allergic skin reaction.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

SECTION 12: Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Toxicity No data on the mixture itself.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility No data available.

Buzzweld DTM (Lead-Free Colours)

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

Buzzweld DTM (Lead-Free Colours)

ADN packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number (ADR/RID) 30

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to applicable. Annex II of MARPOL 73/78 and the IBC Code Not

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance Workplace Exposure Limits EH40.
2018 Code of Practice for the Chemical Agents Regulations (HSA Ireland)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet WEL: Workplace Exposure Limit.
ATE: Acute Toxicity Estimate.
CAS: Chemical Abstracts Service.
DMEL: Derived Minimal Effect Level.
DNEL: Derived No Effect Level.
OELV: Occupational Exposure Limit Value.
PNEC: Predicted No Effect Concentration.
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.

Revision date 15/07/2019

Revision 7

Supersedes date 17/07/2018

SDS number 007

Buzzweld DTM (Lead-Free Colours)

Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H351 Suspected of causing cancer. H360F May damage fertility. H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH208 Contains METHYL ETHYL KETOXIME, COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.
---------------------------	---

The information in this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.